

UltraWood™ Premier and UltraWood™ Elite contribute to the achievement of LEED® credits in the following ways

LEED® BD+C: New Construction (NC) v4.1 & LEED® BD+C: Core and Shell (CS) v4.1

MATERIALS & RESOURCES	Credit 2: Building Product Disclosure and Optimization—Environmental Product Declarations (1-2 points) Credit 3: Building Product Disclosure and Optimization – Sourcing of Raw Materials (1-2 points)	These products have a product specific EPD which conforms to ISO 14025 and EN15804 or ISO 21930 and have at least a cradle to gate scope. These products contain 22% pre-consumer recycled content.
ENERGY & ATMOSPHERE	Credit 2: Optimize Energy Performance (1-18 points)	This product has the following specified thermal resistance value, making it suitable for floor heating installations and capable of enhancing the building's energy performance: UltraWood Premier - thermal resistance of 0.033 m2 K/W UltraWood Elite – thermal resistance of ± 0.035 m2 K/W
INDOOR ENVIRONMENTAL QUALITY	Credit 2: Low-Emitting Materials – Flooring (1-3 points)	These products are FloorScore certified and comply with California Department of Public Health (CDPH) Standard Method v1.2–2017.
ALTERNATIVE COMPLIANCE PATH	International Alternative Compliance Path – REACH Optimization* (1 point) *Projects outside of the USA only	These products do not contain ingredients listed on the REACH Authorization or Candidate list and can be valued at 100% of cost.

LEED® ID+C: Commercial Interiors (CI) v4.1

MATERIALS & RESOURCES	Credit 2: Building Product Disclosure and Optimization—Environmental Product Declarations (1-2 points) Credit 4: Building Product Disclosure and Optimization—Sourcing of Raw Materials (1-2 points)	These products have a product specific EPD which conforms to ISO 14025 and EN15804 or ISO 21930 and have at least a cradle to gate scope. These products contain 22% pre-consumer recycled content.
ENERGY & ATMOSPHERE	Credit 2: Optimize Energy Performance (1-18 points)	These products have the following specified thermal resistance value, making them suitable for floor heating installations and capable of enhancing the building's energy performance: UltraWood Premier - thermal resistance of 0.033 m2 K/W UltraWood Elite – thermal resistance of ± 0.035 m2 K/W
INDOOR ENVIRONMENTAL QUALITY	Credit 2: Low-Emitting Materials – Flooring (1-3 points)	These products are FloorScore certified and comply with California Department of Public Health (CDPH) Standard Method v1.2–2017.