

## TORLYS Re-Use Guarantee Guidelines

Please note the following guidelines for repurposing your TORLYS Smart Floor:

- Vacuum and clean entire floor using [TORLYS EcoCare Cleaner](#).
- Carefully remove the baseboards and transition pieces; set aside furniture to one area of the room.
  - Note: As no glue is involved, the furniture does not have to be fully removed from the room but can be moved from one side to another as the old floor is removed and new one installed.
- As there will be damaged planks as well as many cut pieces, expectations for re-use (depending on the age of your TORLYS Smart Floor) should range between two-thirds to three-quarters of the square footage of the original installation.
- Start unclicking your floor starting at the most convenient point. The [TORLYS Bulldog™ Tool](#) may be useful in the disassembly and re-installation of your TORLYS floor.
- When unclicking your floor:
  1. Carefully lift-up the entire row and then unclick the end joints.
  2. Gently angle the floor upwards to unclick rather than aggressively pulling apart to limit the amount of joint breakage.
    - There may be joint damage during the removal. Separate the planks that have damage from the ones that are in good condition. Planks with joint damage will still be useable, however, joint adhesive will be required to re-install these planks; call TORLYS Technical Services (905 696-2371 or 905 696-2406) for details.
- For all other installation matters, please follow TORLYS Installation instructions, available at [www.torlys.com](http://www.torlys.com).

\*Note: Does not apply to nailed or glued floors, or TORLYS Everest Twist. Not applicable to SuperSolid Hardwood by TORLYS and Marquee Floors by TORLYS.

V2\_16/Feb/2022